



YOUR ELECTRICAL EXPERTS

Schools & Colleges

F4P

FUSION
Lamps and Luminaire

MCG
INDUSTRIAL

HEATSTORE
THE TOTAL ELECTRIC HEATING SOLUTION

Levanté

ADDVENT
THE TOTAL VENTILATION SOLUTION

June - August 2025

F4P 2 - 5 | Fusion Luminaires 5 - 11 | Fusion Lamps 12 - 14 | Heatstore 15 - 16
Levanté 15 - 16 | Heatstore 15 - 16 | Addvent 16 | MCG Industrial 17 - 23

Terms and conditions apply. All products are subject to availability and prices correct at the time of print. All prices are exclusive of VAT.

INSECT CONTROL

Insect Killer

- Aluminium alloy body with large killing grid
- Specially designed for maximum insect attraction
- Mounted: Wall, suspended or freestanding
- Guarantee: 1 Year

Includes:

- Lamps
- Removable collection tray
- Suspension chain



F4P

Code	Wattage	No. of Lamps	Room Coverage	1+	3+
Lamp Type: T8					
2811-1642	16W	2 x 8W	50 m ²	£57.99	£56.56
2811-1645	30W	2 x 15W	100 m ²	£60.04	£58.32
2811-1648	40W	2 x 20W	150 m ²	£76.95	£73.95

For replacement lamps, search 'Flykiller lamps' at cef.co.uk

Delivery options to suit you

Free national delivery on online orders over £50 – Free delivery from your local branch

CLEANING WIPES

Heavy-Duty Wipes

- Removes paint, adhesives, epoxy, PU foam, oil, grease and more from hands, tools and surfaces
- Wipes have scrub and smooth sides
- Scrub face: A super tough cloth that loosens even the most stubborn grime and guarantees faster removal
- Smooth face: Absorbs the grime for a super clean finish
- Refreshing sports fragrance
- Dermatologically tested
- Refill pack contains 90% less plastic than standard tubs
- BS EN 1276



BIG WIPES

Visit cef.co.uk for video demonstration

Code	Description	Pack	1+	6+
Standard Wipes				
2820-8668	Tub	100 Wipes	£14.99	£13.99

Multi-Surface Wipes

- Removes paint, adhesives, epoxy, PU foam, oil, grease and more from hands, tools and surfaces
- Excellent absorbency for cleaning spillages
- Powerful cleaning with built-in skin care
- Refreshing sports fragrance
- Dermatologically tested
- Wipes are 100% biodegradable
- Refill pack contains 90% less plastic than standard tubs
- BS EN 1276



BIG WIPES

Visit cef.co.uk for video demonstrationONLY
£14.25
+VAT

Code	Description	Pack	1+	6+
Standard Wipes				
1777-5757	Tub	80 Wipes	£14.25	£13.25

Power Spray

- Ideal for cleaning larger surfaces or pretreating areas such as walls, floors and uPVC window frames before wiping clean
- Removes paint, adhesives, epoxy, PU foam, oil, grease, bitumen and more from hands, tools and hard surfaces
- A powerful, fast-acting cleaning spray with built-in skin protection
- Dermatologically tested
- Antibacterial and antiviral action
- Uses a biodegradable liquid formula
- BS EN 1276



BIG WIPES

Code	Size	1+
Standard Wipes		
1777-5796	1 Ltr	£13.25

CABLE REELS AND EXTENSION LEADS

Unswitched Extension Leads with Neon

F4P

- Can be wall mounted via rear keyhole slots
- Fitted with a 13A fused plug
- BS 1363/A
- Guarantee: 1 Year



0003-7714

FROM
£7.75
+VAT

Code	No. of Gangs	Surge Protection	Cable Length	1+	10+
0003-7714	4	No	2 m	£7.75	£7.50
0048-7948	4	Yes	2 m	£15.95	£15.75
0003-8107	6	No	2 m	£9.25	£8.95
0048-7951	6	Yes	2 m	£12.25	£11.95

Cassette Extension Reel

F4P

- Thermal cut-out with pushbutton reset
- Max. Current [fully wound]: 3A [fully unwound]: 10A
- BS EN 50525 and BS EN 61242
- Guarantee: 1 Year



ONLY
£22.75
+VAT

Code	No. of Gangs	Cable Length	1+
2211-4477	4	10 m	£22.75

Handbag Style Cable Reel

F4P

- Thermal cut-out with pushbutton reset
- Max. Current [fully wound]: 5A [fully unwound]: 13A
- BS EN 50525 and BS EN 61242
- Guarantee: 1 Year



ONLY
£48.95
+VAT

Code	No. of Gangs	Cable Length	1+
2211-4483	4	25 m	£48.95

Freestanding Cable Reel

F4P

- Thermal cut-out with pushbutton reset
- Max. Current [fully wound]: 5A [fully unwound]: 13A
- BS EN 50525 and BS EN 61242
- Guarantee: 1 Year



ONLY
£92.95
+VAT

Code	No. of Gangs	Cable Length	1+
2211-4480	4	50 m	£92.95

TIME LAG SWITCHES

Columbus® Pneumatic Time Lag Switches

Elkay
Energy Saving Switches & Controls

- No neutral required
- Timer adjustment: 5 secs - 5 mins
- Splashproof shroud kit available – sold separately [0003-6400]
- BS EN 60669-2-3:2006
- Guarantee: 3 Years



Load rating:

- 1,440W [6A] Incandescent lamps and resistive loads
- 720W [3A] LED Lamps

FROM
£26.75
+VAT

Code	Configuration	No. of Wire Connections	1+	3+
0003-7666	Single Contact	3	£26.75	£25.75

16A Pushbutton Time Lag Switches

Elkay
Energy Saving Switches & Controls

- Master switch – can be interlinked with any Elkay slave switches [only one master per circuit]
- Suitable for incandescent and fluorescent lamps and resistive loads
- Illuminated blue locator ring
- One minute countdown LED indicator
- Requires capacitor [2816-2924] for all types of low wattage loads including LED lighting [sold separately]
- Concealed fixing screws
- Timer adjustment: 2 mins - 2 hrs
- BS EN 60669-2-3



0704-0065

FROM
£47.50
+VAT

Code	No. of Wire Connections	1+	3+
Guarantee: 3 Years			
0704-0065	2	£47.95	£46.95
Guarantee: 6 Years			
0704-0113	3	£47.50	£46.50

16A Weatherproof Time Lag Switches IP66

Elkay
Energy Saving Switches & Controls

- Master switch – can be interlinked with any Elkay slave switches [only one master per circuit]
- Commonly used for outdoor patio or infrared heaters and where there is a neutral to control all load types of lighting
- Illuminated blue locator ring
- One minute countdown LED indicator
- Includes backbox with M20 knockouts
- Timer adjustment: 2 mins - 2 hrs
- Guarantee: 6 Years



Code	Type	No. of Wire Connections	1+	3+
0704-0125	Pushbutton	3	£56.75	£55.25

TIME LAG SWITCHES

10A Time Lag Switches

- Suitable for resistive loads and incandescent, fluorescent, CFL and LED lamps
- Can be linked with additional units for two way switching
- Requires 25 mm backbox
- Capacitor will often be required when switching certain types of loads – sold separately [2816-2924]
- Timer adjustment: 2 - 60 mins
- BS EN 60669



2816-2909



2816-2903

F4P

PIR Features:

- Detection angle: 360°
- Detection range: 7 m

NEW

Code	Type	No. of Wire Connections	1+	3+
Guarantee: 3 Years				
2816-2903	Pushbutton	2	£40.92	£39.78
2816-2909	PIR	3	£84.94	£82.58
Guarantee: 6 Years				
2816-2912	Pushbutton	3	£50.36	£48.96
2819-2576	PIR	3	£70.66	£68.70

10A Weatherproof Pushbutton
Electronic Time Lag Switches IP66

- Suitable for resistive loads and incandescent, fluorescent, CFL and LED lamps
- Capacitor will often be required when switching certain types of loads – sold separately [2816-2924]
- Timer adjustment: 2 - 60 mins
- BS EN 60669



F4P

Code	No. of Wire Connections	1+	3+
Guarantee: 3 Years			
2816-2906	2	£71.95	£69.95
Guarantee: 6 Years			
2816-2915	3	£57.50	£55.50

Time Lag Switches

- Saves cost and energy by automatically switching off the lights after a preset period of time
- Replaces existing lighting control
- Timer must be set before installation
- No neutral required
- Requires 25 mm backbox
- Splashproof shroud kit available – sold separately [0003-6400]
- BS EN 60669
- Guarantee: 3 Years



2816-2930



2816-2921

Code	Type	Timer Adjustment	Current Rating	No. of Wire Connections	1+	3+
2816-2930	Pneumatic	5 secs - 5 mins	6A Incandescent - 3A Fluorescent	2	£30.50	£29.50
2816-2921	Electronic	20 secs - 25 mins	5A Incandescent - 5A Fluorescent	2	£42.25	£41.25

Elkay
Energy Saving Switches & Controls

16A Two Wire PIRs

- No neutral required
- Please note: Capacitor [2816-2924] will often be required when switching certain types of loads
- Detection angle: 360°
- Detection range: 5 - 7 m
- Timer adjustment: 2 mins - 2 hrs
- Mounted: Surface or flush backbox [not included]
- Guarantee: 3 Years



Code	Description	Height	Width	Depth	1+	3+
0704-0101	Two Wire	85 mm	85 mm	8 mm	£76.95	£74.95

10A Ceiling PIR

- Neutral required
- Please note: Capacitor will often be required when switching certain types of loads – sold separately [2816-2924]
- Lux and sensitivity adjustment
- Mounting height: 2.4 m
- Detection angle: 360°
- Detection range: 10 m
- Timer adjustment: 10 secs - 1 hr
- Guarantee: 6 Years



Includes:

- White and chrome interchangeable bezels
- Surface mounting backbox

Code	Depth	Ø	Cut Out Ø	1+	3+
2816-2918	72 mm	77 mm	64 mm	£47.25	£46.25

Same day range

Almost 3,000 everyday essential products available in branch to take away today

F4P

FROM
£30.50
+VAT

LIGHTING SUSPENSION KITS AND ACCESSORIES

Easy Lock Lighting Suspension Kit

F4P

- Suitable for battens, NCFs, highbays, lowbays and luminaires
- Quick adjustment pin on clutches [no setting key required]
- Working load: 10 kg per clutch
- Safety factor: 5:1

Kit contents:

- 2 x 3 m x 1 mm Steel cables with loops
- 2 x Easy lock clutches
- 2 x Monkey puzzle suspension clips



Code	1+	10+
2639-6275	£14.75	£13.50

LED PANELS

Backlit LED TP[a] Panels IP20

- Aluminium body with low glare opal polycarbonate diffuser
- Optional emergency conversion pack – sold separately [2628-3835]
- Non-dimmable
- Lamp life: 50,000 hrs
- Mounted: Recessed
- Guarantee: 5 Years [on-site: 1 year]

Includes:

- Plug-and-play driver

***WHILE STOCKS LAST**

Code	Wattage	Lumens	Length	Width	Depth	1+	10+
Standard – Warm White – 3000K							
2676-5536 *	36W	3820 lm	595 mm	595 mm	34 mm	£24.17	£22.96
Standard – Cool White – 4000K							
2676-5530 *	36W	3820 lm	595 mm	595 mm	34 mm	£24.17	£22.96
2676-5518	36W	3820 lm	1195 mm	295 mm	34 mm	£46.75	£44.75
2676-5524	45W	4830 lm	1195 mm	595 mm	34 mm	£78.95	£76.95
Standard – Daylight – 6500K							
2676-5533 *	36W	3820 lm	595 mm	595 mm	34 mm	£24.17	£22.96
2676-5521	36W	3820 lm	1195 mm	295 mm	34 mm	£46.75	£44.75
2676-5527	45W	4830 lm	1195 mm	595 mm	34 mm	£78.95	£76.95
Low Glare UGR19 – Cool White – 4000K							
2821-3963	36W	3600 lm	595 mm	595 mm	34 mm	£29.50	£28.50

40W LED Panel Frame IP20

- Slots into a regular 600 mm x 600 mm aperture, providing an illuminated border around an existing ceiling tile
- Aluminium frame with polycarbonate lens
- Optional emergency conversion pack – sold separately [2628-3835]
- Non-dimmable
- Lumen output: 4,000 lm
- Lamp life: 25,000 hrs
- Mounted: Recessed
- Guarantee: 5 Years

Includes:

- Plug-and-play driver

Code	Length	Width	Depth	1+	10+
Standard – Cool White – 4000K					
2789-8966	595 mm	595 mm	13.5 mm	£26.95	£25.95

emitec
DATA PRODUCTS

A full range of network cabling & accessories

Ask at your local branch for further details

FUSION
Luminaires

2676-5530

FROM
£24.17
+VAT

FUSION
Luminaires

ONLY
£26.95
+VAT

LED COMMERCIAL DOWNLIGHTS AND ACCESSORIES

LED Flexi-Fit Tri-Colour Downlights IP20

- White body with opal polycarbonate diffuser
- Integrated switch to select colour temperatures
- Adjustable spring clips allow recessed mounting in downlight holes
- Selectable colour temperature: Warm white 3000K, cool white 4000K and daylight 6500K
- Interchangeable magnetic bezels available – sold separately
- Mounted: Surface or recessed
- Lamp life: 30,000 hrs
- Guarantee: 2 Years

Includes:

- Integrated driver



Visit cef.co.uk for
video demonstration

FROM
£17.75
+VAT

6W Downlight

- Lumen output: 390, 420 or 450 lm

Code	Depth	Ø	Cut Out Ø	1+	10+
2606-9203	15 mm	140 mm	55 - 100 mm	£17.75	£16.75
Code	Finish			1+	10+
Magnetic Bezel					
2606-9218	Chrome			£4.75	£4.25
2606-9215	Matt Black			£4.75	£4.25
2606-9221	Satin Nickel			£4.75	£4.25

12W Downlight

- Lumen output: 900, 930 or 960 lm

Code	Depth	Ø	Cut Out Ø	1+	10+
2827-5349	15 mm	165 mm	55 - 125 mm	£18.95	£17.95
Code	Finish			1+	10+
Magnetic Bezel					
2827-5343	Chrome			£5.50	£4.95
2827-5340	Matt Black			£5.50	£4.95
2827-5346	Satin Nickel			£5.50	£4.95

18W Downlight

- Lumen output: 1,500, 1,530, or 1,560 lm

Code	Depth	Ø	Cut Out Ø	1+	10+
2604-0979	15 mm	217 mm	55 - 175 mm	£25.95	£24.95
Code	Finish			1+	10+
Magnetic Bezel					
2604-0985	Chrome			£5.95	£5.50
2604-0982	Matt Black			£5.95	£5.50
2604-0988	Satin Nickel			£5.95	£5.50

24W Downlight

- Lumen output: 1,980, 2,010 or 2,040 lm

Code	Depth	Ø	Cut Out Ø	1+	10+
2606-9200	15 mm	290 mm	60 - 250 mm	£37.95	£36.95
Code	Finish			1+	10+
Magnetic Bezel					
2606-9209	Chrome			£7.95	£7.50
2606-9206	Matt Black			£7.95	£7.50
2606-9212	Satin Nickel			£7.95	£7.50

WEEE recycling

Ask in branch or visit
cef.co.uk/waste-recycling



LED BATTENS

Tri-Colour LED Battens IP20

- Steel body with powder-coated finish
- Polycarbonate UV stabilised diffuser
- Quick-release access system with LED array safety cords, for easy installation
- Ideal retrofit option for existing T8 or T5 fixtures
- Colour temperature: Warm white 3000K, cool white 4000K and daylight 6500K
- Lamp life: 50,000 hrs
- Dimensions: 72 mm[W] x 72.5 mm[D]
- Mounted: Surface or suspended
- Guarantee: 5 Years (on-site: 1 year)
[emergency: 2 years]

Microwave features:

- Detection angle [ceiling]: 360°
[wall]: 150°
- Detection range: 10 m
- Timer adjustment: 5 secs, 30 secs,
90 secs, 5 mins, 20 mins or 30 mins



Visit cef.co.uk for
video demonstration

Code	Size	Wattage	Sensor	Lumens	Length	Price		
Standard								
2756-5063	2 ft	10W	No	1200 lm	600 mm	1+	£29.95	10+ £29.20
2756-5066	4 ft	20W	No	2400 lm	1200 mm	1+	£31.95	10+ £31.15
2756-5075	4 ft	40W	No	4800 lm	1200 mm	1+	£48.75	10+ £47.55
2756-5081	5 ft	30W	No	3600 lm	1500 mm	1+	£36.50	10+ £35.60
2756-5093	5 ft	30W	Microwave	3600 lm	1500 mm	1+	£55.50	10+ £54.10
2756-5099	5 ft	60W	No	7200 lm	1500 mm	1+	£50.25	10+ £48.95
2756-5105	5 ft	60W	Microwave	7200 lm	1500 mm	1+	£76.95	10+ £75.05
2756-5111	6 ft	40W	No	4800 lm	1800 mm	1+	£44.95	10+ £43.85
2756-5117	6 ft	67W	No	8040 lm	1800 mm	1+	£64.95	10+ £63.35
3 hr Maintained Emergency								
2756-5072	4 ft	20W	No	2400 lm	1200 mm	1+	£76.95	3+ £75.05
2756-5078	4 ft	40W	No	4800 lm	1200 mm	1+	£94.95	3+ £92.60
2756-5087	5 ft	30W	No	3600 lm	1500 mm	1+	£81.95	3+ £79.90
2756-5096	5 ft	30W	Microwave	3600 lm	1500 mm	1+	£97.50	3+ £95.05
2756-5102	5 ft	60W	No	7200 lm	1500 mm	1+	£92.50	3+ £90.20
2756-5108	5 ft	60W	Microwave	7200 lm	1500 mm	1+	£116.95	3+ £114.05
2756-5114	6 ft	40W	No	4800 lm	1800 mm	1+	£87.25	3+ £85.05
2756-5120	6 ft	67W	No	8040 lm	1800 mm	1+	£102.50	3+ £99.95



LED LINEAR FITTINGS

Aten LED Linear Fittings IP20

- Glass-free lighting solution ideal for kitchens
- Powder-coated aluminium body with PMMA opal diffuser and polycarbonate end caps
- Colour temperature: Cool white 4000K
- Lamp life: 30,000 hrs
- Dimensions: 33 mm[W] x 45 mm[D]
- Mounted: Surface
- Guarantee: 2 Years



FROM
£31.75
+VAT

Code	Size	Wattage	Lumens	Length	1+	10+
1994-9083	2 ft	25W	2000 lm	594 mm	£31.75	£30.95
1994-9077	4 ft	48W	4300 lm	1194 mm	£55.95	£54.50
1994-9080	5 ft	48W	4800 lm	1494 mm	£64.95	£63.50

Aten2 LED Tri-Colour
Linear Fittings IP20

- Glass-free lighting solution ideal for kitchens
- Powder-coated aluminium body with PMMA opal diffuser and polycarbonate end caps
- Selectable colour temperature: Warm white 3000K, cool white 4000K and daylight 6000K
- Switch the unit Off then On within three seconds and the fitting will switch between colour temperatures
- Once desired colour is selected, leave on for ten seconds and the fitting will remember desired colour
- Lamp life: 30,000 hrs
- Dimensions: 133 mm[W] x 45 mm[D]
- Mounted: Surface
- Guarantee: 2 Years



Code	Size	Wattage	Lumens	Length	1+	10+
1994-9083	2 ft	25W	1900 lm / 2100 lm / 2200 lm	594 mm	£33.95	£32.50
1994-9077	4 ft	48W	3600 lm / 3800 lm / 4000 lm	1194 mm	£61.50	£60.05
1994-9080	5 ft	48W	4100 lm / 4500 lm / 4700 lm	1494 mm	£67.75	£66.25

LED NON-CORROSIVE FITTINGS

LED Non-Corrosive Fittings IP65

- Polycarbonate body and purpose-designed opal diffuser
- Colour temperature: Cool white 4000K
- Lamp life: 50,000 hrs
- Impact rating: IK08
- Mounted: Surface or suspended
- Warranty: 5 Years [on-site: 1 year]
[emergency: 2 years]

Microwave features:

- Detection angle [ceiling]: 360°
[wall]: 150°
- Detection range: 10 m
- Timer adjustment: 5 secs, 30 secs,
90 secs, 5 mins, 20 mins or 30 mins

Includes:

- Stainless steel fixing clips
- Gear tray extension cords



Code	Size	Wattage	Lumens	Length	Width	Depth	Price		
Standard									
2613-7831	2 ft	9W	1100 lm	600 mm	96 mm	79 mm	1+	£23.48	10+ £22.46
2613-7834	2 ft	18W	2200 lm	600 mm	96 mm	79 mm	1+	£30.19	10+ £28.88
2613-7894	4 ft	18W	2200 lm	1200 mm	96 mm	79 mm	1+	£31.81	10+ £30.43
2613-7840	4 ft	40W	4800 lm	1200 mm	96 mm	79 mm	1+	£42.07	10+ £40.24
2613-7846	5 ft	23W	2800 lm	1500 mm	96 mm	79 mm	1+	£36.61	10+ £35.02
2613-7852	5 ft	48W	5800 lm	1500 mm	96 mm	79 mm	1+	£47.82	10+ £45.74
2613-7858	6 ft	27W	3200 lm	1800 mm	96 mm	83 mm	1+	£44.95	10+ £42.99
2613-7864	6 ft	55W	6600 lm	1800 mm	96 mm	83 mm	1+	£65.65	10+ £62.79
Standard – Microwave Sensor									
2726-9278	5 ft	23W	2800 lm	1500 mm	96 mm	79 mm	1+	£60.85	10+ £58.21
2726-9272	5 ft	48W	5800 lm	1500 mm	96 mm	79 mm	1+	£74.65	10+ £71.41
3 hr Maintained Emergency									
2613-7837	4 ft	18W	2200 lm	1200 mm	96 mm	79 mm	1+	£71.88	3+ £68.75
2613-7843	4 ft	40W	4800 lm	1200 mm	96 mm	79 mm	1+	£87.40	3+ £83.60
2613-7849	5 ft	23W	2800 lm	1500 mm	96 mm	79 mm	1+	£79.54	3+ £76.08
2613-7855	5 ft	48W	5800 lm	1500 mm	96 mm	79 mm	1+	£93.25	3+ £89.19
2613-7861	6 ft	27W	3200 lm	1800 mm	96 mm	83 mm	1+	£89.99	3+ £86.08
2613-7867	6 ft	55W	6600 lm	1800 mm	96 mm	83 mm	1+	£112.99	3+ £108.08
3 hr Maintained Emergency – Microwave Sensor									
2726-9281	5 ft	23W	2800 lm	1500 mm	96 mm	79 mm	1+	£106.09	3+ £101.48
2726-9275	5 ft	48W	5800 lm	1500 mm	96 mm	79 mm	1+	£124.10	3+ £118.71



LED UNDER CUPBOARD AND CABINET LIGHTING

LED Slimline Colour Selectable Under Cabinet Lights IP20

- Suitable replacement for traditional T4 and T5 fluorescent fittings
- Compact, surface mounted design
- Selectable colour temperature:
Warm white 3000K and cool white 4000K
- Beam angle: 150°
- Lamp life: 30,000 hrs
- Warranty: 3 Years

Includes:

- 1.5 m Mains cable
- 170 mm Link cable
- Fixing brackets
- Connector

Code	Wattage	Length	Lumens	1+	5+
2795-8372	4W	225 mm	400 lm	£15.95	£15.50
2795-8369	4W	288 mm	450 lm	£17.50	£17.05
2795-8378	7W	516 mm	850 lm	£20.95	£20.50
2795-8360	13W	849 mm	1500 lm	£25.95	£25.25
2795-8363	18W	1149 mm	1800 lm	£29.95	£29.25



CCT Colour Select

Link Cables

- For use with Fusion under cabinet lights



Code	Length	1+	5+
2795-8366	250 mm	£2.22	£2.15
2795-8375	500 mm	£3.34	£3.23
2795-8357	1000 mm	£4.45	£4.30



ALL PRICES EXCLUDE VAT

BULKHEADS

12W / 16W Dome LED Tri-Colour Bulkheads IP65

- Polycarbonate body and opal diffuser
- Screwless twist-and-lock bezel
- Selectable colour temperature: Warm white 3000K, cool white 4000K and daylight 6500K
- Switch located on the driver takes the fitting down to 12W for increased energy savings
- Lumen output [12W]: 1,200 - 1,300 lm
[16W]: 1,600 - 1,700 lm
- Warranty: 5 Years [on-site: 1 year]
[emergency: 2 years]

Code	Sensor	Lamp Life	Depth	Ø	Price			
Standard								
2704-3078	No	30000 hrs	82.5 mm	320 mm	1+	£23.60	5+	£22.15
2704-3147	Microwave	30000 hrs	82.5 mm	320 mm	1+	£42.95	5+	£40.95
3 hr Maintained Emergency								
2704-3144	No	20000 hrs	82.5 mm	320 mm	1+	£44.60	3+	£42.60
2704-3150	Microwave	20000 hrs	82.5 mm	320 mm	1+	£64.95	3+	£62.95
Code	Colour					1+	3+	
Bezels – To Be Ordered Separately								
2722-3345	Chrome					£7.95	£7.75	
2722-3348	Polished Brass					£12.95	£12.75	

- Microwave features:
- Detection angle: 360°
 - Detection range: 10 m
 - Timer adjustment: 5 secs - 10 mins



Visit cef.co.uk for video demonstration

FROM
£23.60
+VAT

LED EMERGENCY LIGHTING AND ACCESSORIES

LED Emergency Bulkheads IP65

- High quality polycarbonate body and diffuser with hinged gear tray
- LiFePO4 battery technology greatly improves operational life and charging cycle capacity
- Emergency duration: 3 hrs
- Colour temperature: Daylight 6500K
- Emergency lumen output: 110 lm [maintained / non-maintained only]
- Lumen output: 170 lm
- Lamp life: 30,000 hrs
- Mounted: Surface
- Warranty: 2 Years

Code	Wattage	Type	Emergency Type	Height	Width	Depth	1+	3+
2816-1985	1.1W	Standard	Non-Maintained	107 mm	349 mm	64 mm	£16.50	£15.95
2816-1979	2.3W	Standard	Maintained / Non-Maintained	107 mm	349 mm	64 mm	£17.95	£17.50
2816-1982	2.3W	Auto Self-Test	Maintained / Non-Maintained	107 mm	349 mm	64 mm	£22.95	£22.50

Includes:

- ISO 7010 Legend pack

2.7W LED 5-In-1 Maintained / Non-Maintained Emergency Droplights IP20



- Polycarbonate housing
- Test button and charge indicator LED
- Emergency duration: 3 hrs
- Emergency lumen output: 14 lm
- Lumen output: 23 lm
- Lamp life: 30,000 hrs
- Mounted: Ceiling, suspended, recessed, side or wall
- Guarantee: 2 Years



Code	Type	Legend	Height	Width	Depth	1+	3+
2658-8812	Standard	Exit Arrow Up	180 mm	264 mm	28 mm	£35.95	£33.95

3W LED Non-Maintained Emergency Twinspots IP65



- Polycarbonate construction
- LiFePO4 battery technology greatly improves operational life and charging cycle capacity
- Emergency duration: 3 hrs
- Colour temperature: Daylight 6500K
- Lumen output: 297 lm
- Lamp life: 30,000 hrs
- Guarantee: 2 Years



Code	Type	Height	Width	Depth	1+	3+
2658-8821	Standard	281 mm	297 mm	89 mm	£45.50	£43.50

LED EMERGENCY LIGHTING AND ACCESSORIES

3.5W LED Maintained / Non-Maintained Emergency Exit Boxes IP20

- Polycarbonate housing and diffuser
- LiFePO4 battery technology greatly improves operational life and charging cycle capacity
- Emergency duration: 3 hrs
- Colour temperature: Daylight 6500K
- Emergency lumen output: 20 lm
- Lumen output: 35 lm
- Lamp life: 30,000 hrs
- Guarantee: 2 Years



Code	Type	Legend	Height	Width	Depth	1+	3+
2745-0358	Standard	Exit Arrow Up	185 mm	330 mm	39 mm	£32.75	£31.75

1W LED Non-Maintained Emergency Downlights IP20

- Typically used as an indoor escape route emergency light to help guide occupants from a building
- Interchangeable lenses available to suit specific settings – sold separately
- Emergency duration: 3 hrs
- Colour temperature: Daylight 6500K
- Lumen output: 121 lm
- Lamp life: 30,000 hrs
- Mounted: Recessed
- Guarantee: 2 Years



Includes:
■ Battery pack and driver



Visit cef.co.uk for video demonstration

Code	Type	Beam Angle	Depth	Ø	Cut Out Ø	1+	3+
2628-8332	Standard	120°	50 mm	50 mm	45 mm	£29.95	£27.95

Need a product datasheet?

Download at cef.co.uk

LED FLOODLIGHTS

Guardian LED Floodlights IP65

- Die-cast aluminium powder-coated body
- Ground spike and extension arm sold separately [only compatible with Floodlights up to 50W]
- Can be mounted without removing the bracket
- Colour temperature: Cool white 4000K
- Lamp life: 50,000 hrs
- Guarantee: 5 Years [on-site: 1 year]



2672-6728

Includes:

- Adjustable bracket
- 1 m Cable



Visit cef.co.uk for video demonstration

Code	Wattage	Lumens	Height	Width	Depth	1+	3+
C							
2672-6707	15W	1950 lm	198 mm	129 mm	34 mm	£24.50	£23.50
2672-6719	30W	3900 lm	246 mm	173 mm	42 mm	£37.75	£36.75
2672-6728	50W	6500 lm	255 mm	188 mm	42 mm	£56.50	£54.95
2672-6734	80W	10400 lm	302 mm	250 mm	52 mm	£111.50	£108.50
2672-6704	100W	13000 lm	358 mm	279 mm	57 mm	£126.95	£123.95
2672-6710	150W	19500 lm	405 mm	329 mm	62 mm	£156.50	£153.50
2672-6716	250W	32500 lm	471 mm	401 mm	62 mm	£241.95	£238.95



ALL PRICES EXCLUDE VAT

LED WALL PACKS

20W Tri-Colour LED Wall Packs IP65

- Die-cast aluminium body and polycarbonate diffuser
- Push-fit connectors for easy installation
- Selectable colour temperature: Warm white 3000K, cool white 4000K or daylight 6500K
- Lumen output: 1,500, 1,550 or 1,600 lm
- Lamp life: 50,000 hrs
- Guarantee: 5 Years [on-site: 1 year]



CCT Colour Select



Visit cef.co.uk for video demonstration

Code	Sensor	Height	Width	Depth	1+	3+
2641-1884	No	221 mm	207 mm	82 mm	£79.95	£77.95
2641-1887	Photocell	221 mm	207 mm	82 mm	£89.25	£87.25

Branch opening hours

Mon-Fri 7:30-5:30 Sat 8:30-12:00

[local exceptions may apply]



LED STREET LIGHTING AND ACCESSORIES

Nano LED Road Lanterns IP66

- Die-cast aluminium with polycarbonate lens
- Type: Post top
- Surge protection as standard
- Tool-free maintenance
- Lighting distribution: Type II
- Colour temperature: Cool white 4000K
- Lamp life: 50,000 hrs
- Impact rating: IK08
- Mounted: 60 mm(Ø) Spigot
- Guarantee: 5 Years [on-site: 1 year]

Code	Wattage	Lumens	Length	Width	Depth	1+	3+
Standard							
2275-5130	40W	4400 lm	490 mm	176 mm	78 mm	£176.31	£172.12
2275-5136	60W	6600 lm	490 mm	176 mm	78 mm	£184.72	£180.32
Photocell							
2275-5133	40W	4400 lm	490 mm	176 mm	78 mm	£218.32	£213.12
2275-5139	60W	6600 lm	490 mm	176 mm	78 mm	£226.71	£221.32
2523-2107	80W	8800 lm	610 mm	270 mm	76 mm	£293.92	£286.92
2523-2104	120W	13200 lm	610 mm	270 mm	76 mm	£327.51	£319.72
Code	Height		Ø			1+	3+
NEMA Socket Blanking Cap							
2523-2110	55 mm		80 mm			£10.95	£10.50



BOLLARDS

20W / 24W LED Bollard IP65

- Powder-coated aluminium bollard with clear diffuser
- Wattage selectable on-site for improved energy savings
- Colour temperature: Cool white 4000K
- Lumen output [20W]: 1,200 lm
[24W]: 1,500 lm
- Lamp life: 50,000 hrs
- Mounted: Root
- Warranty: 5 Years [on-site: 1 year]

Includes:

- 'J' Bolts
- Fixings
- Base plate
- 1.2 m Prewired cable



Code	Height	Ø	1+	3+
2719-0774	1000 mm	160 mm	£176.95	£173.95

Commercial Bollard IP65

- Die-cast aluminium bollard with clear PMMA diffuser
- Lamp type: ES / E27 [not included]
- Max. LED Lamp wattage: 15W
- Mounted: Root
- Guarantee: 5 Years

Includes:

- 'J' Bolts
- Fixings
- Base plate
- 1 m Prewired cable



Code	Height	Ø	1+	3+
2771-7172	1015 mm	160 mm	£119.95	£116.95

Click & collect

At any branch in the UK



INSECT KILLER LAMPS

Insect Killer Tubes 230V



- It is recommended that insect killer lamps are changed every 12 months as UV levels deteriorate over the life of the lamp
- Deterioration of the lamp means insect attraction rates are significantly reduced
- Lamp life: 8,000 hrs



Code	Length	Wattage	1+	10+
T5				
2090-7061	12"	8W	£11.77	£11.18
T8				
2088-5029	18"	15W	£11.57	£11.05
2094-6910	2 ft	18W	£12.92	£12.40

Essential LED GU10 Lamps 230V
– Pack of 10

- Suitable replacement for 35 and 50W halogen lamps
- Beam angle: 38°
- Lamp life: 20,000 hrs
- Guarantee: 2 Years



NEW

Code	Wattage	Lumens	Colour Temp	Equivalent Price Each	1+
Non-Dimmable					
2818-4602	3.7W	352 lm	Warm White – 3000K	£1.68	£16.75
2818-4515	3.7W	352 lm	Cool White – 4000K	£1.68	£16.75
2818-4590	3.7W	352 lm	Daylight – 6000K	£1.68	£16.75
Dimmable					
2818-4608	3.7W	352 lm	Warm White – 3000K	£2.28	£22.75
2818-4584	3.7W	352 lm	Cool White – 4000K	£2.28	£22.75
2818-4596	3.7W	352 lm	Daylight – 6000K	£2.28	£22.75



ALL PRICES EXCLUDE VAT

LED CAPSULE LAMPS

2W LED G4 Capsule Lamp
– Pack of 2

- Suitable replacement for 10 and 20W halogen lamps
- Lamp life: 15,000 hrs
- Guarantee: 1 Year



ONLY
£10.50
+VAT

Code	Lumens	1+	10+
Non-Dimmable – Warm White – 3000K			
2196-2761	200 lm	£10.50	£9.95

3.3W LED G9 Capsule Lamp
– Pack of 2

- Suitable replacement for 40W halogen lamps
- Lamp life: 15,000 hrs
- Guarantee: 1 Year



ONLY
£10.95
+VAT

Code	Lumens	1+	10+
Non-Dimmable – Warm White – 3000K			
2196-2764	350 lm	£10.95	£10.50

2.6W LED GY6.35 Capsule Lamp 12V



- Suitable replacement for 35W halogen lamps
- Lamp life: 15,000 hrs
- Guarantee: 1 Year



Code	Lumens	1+	10+
Non-Dimmable – Warm White – 3000K			
2786-2006	300 lm	£7.50	£6.95

**Over 390
branches
nationwide**



There's always a branch near you

LED TUBES

LED T8 Tri-Colour Glass Tubes

- Suitable replacement for fluorescent tubes
- Complete with LED starter for use in switch start retrofit installations
- Selectable colour temperature: Warm white 3000K, cool white 4000K and daylight 6500K
- Beam angle: 300°
- Lamp life: 25,000 hrs
- Guarantee: 3 Years

Code	Length	Wattage	Lumens	1+	5+
Non-Dimmable					
2772-8017	2 ft	9W	1080 lm	£8.05	£7.75
2772-8020	3 ft	14W	1680 lm	£11.25	£10.80
2772-8023	4 ft	18W	2160 lm	£13.95	£13.50
2772-8026	5 ft	24W	2880 lm	£16.35	£15.65
2772-8029	6 ft	30W	3600 lm	£29.95	£28.95




FROM
£8.05
+VAT

LED LAMPS

8W G24 LED Lamps

- Suitable replacement for 18 and 26W compact fluorescent lamps
- Rotating end cap
- Lamp life: 25,000 hrs
- Guarantee: 3 Years



Code	Cap	Length	Lumens	1+	10+
Non-Dimmable – Cool White – 4000K					
2275-5286	G24 2 Pin	145 mm	800 lm	£16.95	£16.50
2275-5325	G24 4 Pin	145 mm	800 lm	£16.95	£16.50

LED Retrofit Discharge Lamps


- Suitable replacement for 70W HID lamps
- Beam angle: 300°
- Lamp life: 25,000 hrs
- Guarantee: 3 Years



Code	Wattage	Cap	Length	Ø	Lumens	1+
Non-Dimmable – Daylight – 6000K						
1414-1569	11W	ES / E27	165 mm	65 mm	1150 lm	£45.75
2253-2830	15W	ES / E27	165 mm	65 mm	1575 lm	£49.95

LED 2D Lamps

- Suitable replacement for 16, 28 and 38W compact fluorescent 2D lamps
- Lamp life: 30,000 hrs
- Guarantee: 3 Years



FROM
£19.75
+VAT

Code	Wattage	Cap	Lumens	1+	10+
Non-Dimmable – Cool White – 4000K					
2123-0989	8W	GR8 2 Pin	800 lm	£19.75	£18.75
2123-0992	8W	GR10q 4 Pin	800 lm	£19.75	£18.75
2123-0980	14W	GR8 2 Pin	1400 lm	£21.95	£20.95
2123-0983	14W	GR10q 4 Pin	1400 lm	£21.95	£20.95
2123-0986	18W	GR10q 4 Pin	2000 lm	£26.95	£25.95

WEEE recycling

Ask in branch or visit
cef.co.uk/waste-recycling

LED LAMPS

LED Retrofit Discharge Lamps

- Suitable replacement for lowbays, highbays, floodlights and lantern HID lamps
- Beam angle: 300°
- Guarantee: 3 Years
- Lamp life: 25,000 hrs

Code	Wattage	Cap	Length	Ø	Lumens	Replacement For	1+
Non-Dimmable – Daylight – 6000K							
2448-1897	20W	ES / E27	178 mm	93 mm	2600 lm	70W HID	£48.95
2448-1903	30W	ES / E27	188 mm	93 mm	3900 lm	70 - 150W HID	£60.85
2448-1900	30W	GES / E40	208 mm	93 mm	3900 lm	70 - 150W HID	£60.85
2448-1906	60W	GES / E40	280 mm	93 mm	8000 lm	250W HID	£73.75
2448-1909	85W	GES / E40	285 mm	106 mm	11000 lm	250 - 400W HID	£88.50
2448-1891	100W	GES / E40	288 mm	120 mm	13000 lm	250 - 400W HID	£98.50
2448-1894	120W	GES / E40	308 mm	120 mm	15000 lm	400W HID	£114.95

2448-1903



FUSION Lamps



2448-1891

FROM
£48.95
+VAT

8W LED G12 Discharge Lamp

FUSION Lamps

- Suitable replacement for 35 - 70W metal halide lamps
- Beam angle: 270°
- Lamp life: 30,000 hrs
- Guarantee: 3 Years



Code	Length	Ø	Lumens	1+
Non-Dimmable – Cool White – 4000K				
2612-4382	95 mm	30 mm	1100 lm	£33.50

2G11 LED PLL Lamps

FUSION Lamps

- Suitable replacement for 18 - 55W compact fluorescent lamps
- Lamp life: 20,000 hrs
- Guarantee: 3 Years



Code	Length	Length	Lumens	1+	10+
Non-Dimmable – Cool White – 4000K					
1653-8089	8W	225 mm	900 lm	£15.75	£15.25
2345-5771	12W	315 mm	1350 lm	£16.25	£15.75
653-5578	16W	415 mm	1800 lm	£16.95	£16.50
2345-5777	20W	540 mm	2350 lm	£17.95	£17.50

INFRARED HEAT LAMPS

R7s Infrared Heat Lamp

FUSION Lamps

- Cap: R7s



Code	Length	Wattage	Lamp Life	1+	10+
Clear					
0305-6371	118 mm	300W	1000 hrs	£13.76	£12.73

R7s Protected Infrared Lamp

FUSION Lamps

- Protective glass sleeve around the lamp
- Cap: R7s



ONLY
£29.18
+VAT

Code	Length	Wattage	Lamp Life	1+	10+
0648-1090	118 mm	300W	4000 hrs	£29.18	£28.15

R125 Infrared Heat Lamp

FUSION Lamps

- Cap: ES / E27
- Lamp life: 5,000 hrs



ONLY
£12.18
+VAT

Code	Wattage	1+	10+
Clear			
0531-3706	250W	£12.18	£11.40

Free tea, coffee & Wi-Fi
When you visit our branches



PANEL HEATERS

Low Surface Temperature Panel Heaters

HEATSTORE



- Durable, slim and contemporary design
- Suitable for healthcare applications as maximum surface temperature is limited to 43°C
- Seven day electronic timer with six On / Off periods per day
- Four operating modes: Programme, boost, setback and manual
- Intelligent fan control automatically adjusts fan speed to eliminate pushing out cool air on start up
- Fan only mode for air circulation
- Concealed, easy-to-read display with electronic child lock
- Open window technology
- Mounted: Wall
- IP24
- Complies with Lot 20
- On-site warranty: 2 Years



Includes:

- Hinged wall bracket
- 1.1 m Cable

Code	Power Rating	Height	Width	Depth	1+	3+
2776-1053	500W	430 mm	506 mm	93 mm	£305.86	£301.74
2776-1059	750W	430 mm	506 mm	93 mm	£317.19	£313.07
2776-1038	1kW	430 mm	640 mm	93 mm	£328.52	£324.40
2776-1044	1.5kW	430 mm	892 mm	93 mm	£376.93	£372.81

DESK FANS

Oscillating Desk Fans

Levante

- Adjustable tilt
- Operation type: Piano switch
- Guarantee: 1 Year



Includes:

- 1.5 m Cable and plug

Code	Size	Power Rating	No. of Speeds	1+	3+
2756-9824	9"	30W	2	£22.14	£21.06
2756-9803	12"	40W	3	£23.71	£22.63

Branch opening hours

Mon-Fri 7:30-5:30 Sat 8:30-12:00

[local exceptions may apply]

HAND DRYERS

1.1 kW ABS High-Speed Hand Dryer

HEATSTORE

- Sensing distance: 100 mm
- Drying time: 10 secs
- Dimensions: 248 mm[H] x 250 mm[W] x 114 mm[D]
- IPX1
- Exchange warranty: 2 Years



Code	Air Speed	Decibel Rating	1+	2+
2148-9250	90 m/s	68 dB[A] @ 1 m	£138.99	£135.88

1.8 kW High-Speed Hand Dryers

HEATSTORE

- Sensing distance: 120 mm
- Drying time: 10 secs
- Dimensions: 320 mm[H] x 290 mm[W] x 170 mm[D]
- IPX1
- Exchange warranty: 2 Years



ONLY
£172.91
+VAT

Code	Air Speed	Decibel Rating	1+	2+
2148-9253	90 m/s	75 dB[A] @ 1 m	£172.91	£169.69

1.5 kW ABS Hand Dryer

Levante

- Sensing distance: 100 mm
- Drying time: 30 - 45 secs
- Dimensions: 243 mm[H] x 194 mm[W] x 135 mm[D]
- IP22
- Guarantee: 1 Year



Code	Air Speed	Decibel Rating	1+	2+
1010-8993	14.5 m/s	75 dB[A] @ 1 m	£77.26	£74.03

2.5 kW Brushed Stainless Steel Hand & Face Dryer

Levante

- 360° Swivel nozzle
- Sensing distance: 100 mm
- Drying time: 30 - 45 secs
- Dimensions: 240 mm[H] x 270 mm[W] x 190 mm[D]
- IPX1
- Guarantee: 1 Year



Code	Air Speed	Decibel Rating	1+	2+
1015-3111	30 m/s	85 dB[A] @ 1 m	£158.70	£155.45

HAND DRYERS

1.5 kW ABS Hand Dryer

- Sensing distance: 120 mm
- Drying time: 60 secs
- Dimensions: 282 mm[H] x 225 mm[W] x 160 mm[D]
- IPX1
- Guarantee: 2 Years

ADDVENT

ONLY
£84.91
+VAT

Code	Air Speed	Decibel Rating	1+	2+
2149-2910	12 m/s	45 dB[A] @ 1.5 m	£84.91	£81.81

2.3 kW ABS Hand Dryer

- Sensing distance: 120 mm
- Drying time: 60 secs
- Dimensions: 235 mm[H] x 267 mm[W] x 210 mm[D]
- IPX1
- Guarantee: 2 Years

ADDVENT



Code	Air Speed	Decibel Rating	1+	2+
2149-2913	20 m/s	65 dB[A] @ 1.5 m	£110.49	£107.35

3-IN-1 AIR CONDITIONER, COOLING FAN & DEHUMIDIFIERS

3-In-1 Portable Air Conditioner, Cooling Fan and Dehumidifier

ADDVENT

- Compact, portable air conditioning unit with HEPA filter, castors and handle
- Complete air quality solution for use in areas up to 20 m²
- Speeds: 2
- Programmable timer: 24 hr
- Easily adjust settings via the remote control handset (included)
- Power rating: 1 kW
- Operating temperature: 18 - 32°C
- 9,000 BTU
- Sleep mode
- Exchange warranty: 1 Year



Includes:

- Window fitting kit
- Continuous draining hose
- Remote control
- 1.5 m Exhaust hose

ONLY
£415.14
+VAT

Code	Extraction	Capacity	Decibel Rating	Height	Width	Depth	1+
2248-7518	22 Ltrs per Day	0.5 Ltr	65 dB	770 mm	317 mm	402 mm	£415.14

AIR CURTAINS

Surface Air Curtain

- For installation above external doors to reduce heat loss
- Three heat settings
- Fan only setting for air circulation
- Overheat safety cut-out
- On-site warranty: 2 Years

Includes:

- Adjustable mounting bracket



HEATSTORE

Code	Power Rating	Decibel Rating	Airflow	Height	Width	Depth	1+	3+
0546-2002	3 kW	46 dB[A] @ 1 m	185 m ³ /h	211 mm	622 mm	115 mm	£263.50	£258.25

ONLY
£263.50
+VAT

3 kW Surface Air Curtain

- Suitable for small doorways
- Two heat settings
- Fan only setting for air circulation
- Overheat safety cut-out
- Mounted: Wall or ceiling
- Guarantee: 2 Years

Includes:

- Adjustable mounting bracket
- 1.5 m Cable



Levante

Code	Decibel Rating	Airflow	Height	Width	Depth	1+	3+
230V [Single Phase]							
1627-9894	60 dB[A] @ 300 mm	254 m ³ /h	210 mm	580 mm	106 mm	£98.95	£95.50

ONLY
£98.95
+VAT

SURGE ARRESTERS

Four Module Surge Protection Device

- Suitable for use with most brands of distribution boards
- Protects against indirect lightning effects and transient surges
- Prolongs the life of appliances and sensitive electronic equipment
- Visual and remote end-of-life indication
- Recommended backup MCB: 32A
- Mounted: DIN rail
- BS EN 61643-11 and BS EN 62305
- Warranty: 10 Years
[enclosure: 1 Year]

MCG
INDUSTRIAL

18th
EDITION



Code	Height	Width	Depth	No. of Ways	1+
Device Complete with Metal Enclosure [IP20]					
2441-3887	175 mm	110 mm	82 mm	4	£122.50

Single Module Surge Protection Device

- Suitable for use with most brands of distribution units
- Protects against indirect lightning effects and transient surges
- Prolongs the life of appliances and sensitive electronic equipment
- Visual end-of-life indication
- Recommended backup MCB: 16 - 32A
- SPD Complete with metal enclosure
[2441-3893] includes one spare way for backup MCB
- Mounted: DIN rail
- BS EN 61643-11 and BS EN 62305
- Warranty: 10 Years
[enclosure: 1 Year]

MCG
INDUSTRIAL

18th
EDITION



Code	Type	Suitable For	No. of Poles	No. of Modules	1+
2433-7003	2 + 3	TN-S, TN-C-S and TT	1P+N	1	£48.25

Surge Protection Device with Backup MCB

- Suitable for use with most brands of consumer units
- Protects against indirect lightning effects and transient surges
- Prolongs the life of appliances and sensitive electronic equipment
- Visual and remote end-of-life indication
- Backup MCB rating: 32A
- Mounted: DIN rail
- BS EN 61643-11
- Warranty: 1 Year

MCG
INDUSTRIAL

18th
EDITION



Visit cef.co.uk for
video demonstration

Code	Type	Suitable For	1+
Device with Cables and 32A B Curve MCB [6 kA]			
2696-8078	2	TN-S, TN-C-S and TT Earthing	£33.75

MOTOR STARTERS AND ACCESSORIES

400V DC Injection Braking Module

- Controlled stopping in compliance with PUWER 98
- Can be used to retrofit and to integrate with existing controls
- Simple braking time and torque setting
- Direct on line or star-delta systems
- BS EN 60947

Crompton
controls



Code	Height	Width	Depth	1+
0577-6315	81 mm	45 mm	121 mm	£349.95

400V DOL DC Injection Braking Units with Overload

- Robust, pressed steel enclosure with removable lid and large Start / Stop buttons
- Start, protect and safety stop for standard rotating machines
- Controlled stopping in compliance with PUWER 98 [not for instant motor stopping applications]
- Simple braking time and torque setting
- Suitable for up to twelve stops per hour
- Mounted: Surface
- IP55
- BS EN 60947

Crompton
controls



Code	kW Rating	Overload Rating	1+
1033-2955	2.2 kW	4 - 6A	£619.95
1033-2964	5.5 kW	10 - 13A	£676.95

Enclosed Contactors

- Ideal for heating and lighting applications
- Pressed steel enclosure: RAL7035
- Top and bottom cable gland knockouts
- IP55
- BS EN 60947

Crompton
controls



Code	Current Rating AC1	Contact Configuration	Height	Width	Depth	1+
3 Pole + N with Fuse Protection						
0013-4635	25A	3 NO	184 mm	184 mm	149 mm	£115.75
0013-4638	40A	3 NO	184 mm	184 mm	149 mm	£148.50
4 Pole with Neutral Block						
2077-3264	25A	4 NO	184 mm	184 mm	149 mm	£129.95

MODULAR CONTACTORS

Modular Contactors

- Ideal for switching heating and lighting applications
- Coil voltage: 230V AC
- Mounted: DIN rail
- BS EN 61095

1469-6029

FROM
£20.95
 +VAT

Code	Current Rating	No. of Modules	Contact Configuration	1+
2 Pole				
1469-6029	20A	1	2 NO	£20.95
4 Pole				
1469-4562	25A	2	4 NO	£34.10
1462-6381	40A	3	4 NO	£45.75

TIME SWITCHES

16A 7 Day / 24 Hour Time Switch

- Ideal for controlling heating, lighting and security applications
- Six On / Off programmes per day
- Manual override
- Min. Switching time: 1 min
- Battery backup: 100 hrs
- Volt-free contact
- Load rating: 16A [2A inductive]
- Mounted: DIN rail
- BS EN 60730-1

ONLY
£25.75
 +VAT

Code	No. of Channels	1+
2292-7510	1	£25.75

Same day delivery

If ordered before 12:00pm

COMPRESSION GLANDS

Nylon Glands with Locknut IP68

- For use with round cable only
- Supplied with washer and locknut
- Operating temperature: -40 to 100°C [intermittent to 120°C]
- BS EN 62444

FROM
£9.35
 +VAT

Code	Thread Size	Colour	Cable Size Ø	Pack	1+	5+
0070-2535	20 mm	Black	6 - 12 mm	10	£9.35	£9.05
0013-6687	20 mm	Grey	6 - 12 mm	10	£9.35	£9.05
0070-2538	20 mm	Red	6 - 12 mm	10	£9.35	£9.05
0070-2541	20 mm	White	6 - 12 mm	10	£9.35	£9.05
0070-2553	25 mm	Black	13 - 18 mm	10	£12.75	£12.25
0070-2571	32 mm	Black	16 - 21 mm	10	£21.25	£20.05

DIN RAIL ENCLOSURES AND ACCESSORIES

Metalclad DIN Rail Enclosures IP20

- Non-combustible metalclad enclosure
- Multiple knockouts for cable entry
- Raised keyholes for easy installation
- BS EN 61439-3



Includes:

- DIN rail
- Earth bar

Code	No. of Modules	Height	Width	Depth	1+
Top Hinged Door					
2191-0543	4	175 mm	110 mm	82 mm	£22.25
2191-0540	4	225 mm	115 mm	82 mm	£24.75

Metalclad DIN Rail Enclosure IP65

- Non-combustible metalclad enclosure
- Multiple knockouts for cable entry
- Raised keyholes for easy installation
- BS EN 61439-3



Includes:

- DIN rail
- Neutral and earth terminals
- Busbar

Code	No. of Modules	Height	Width	Depth	1+
Top Hinged Door					
2275-1353	4	220 mm	140 mm	100 mm	£33.25

METALCLAD CONSUMER UNITS AND ACCESSORIES

Mains Incomer - Surge Protected

- Non-combustible metalclad consumer units
- Ferruled cable ends for secure connections
- Knockouts: M25, M32 and M40
- IP20
- BS EN 61439-3



SPD Fitted



Includes:

- 100A 2 Pole isolator
- Type 2 surge protection device – [2696-8078]
- Backup 32A B curve MCB [6 kA]

Code	No. of Ways	Height	Width	Depth	1+
2711-1355	4	235 mm	233 mm	110 mm	£52.50
2713-0027	12	235 mm	377 mm	110 mm	£83.25
2713-0030	14	235 mm	377 mm	110 mm	£84.95

Mains Incomer

- Non-combustible metalclad consumer units
- Knockouts: M25, M32 and M40
- IP20
- BS EN 61439-3



Includes:

- 2 Pole isolator

Code	No. of Ways	Height	Width	Depth	1+
100A Isolator – Single Row					
2073-7342	2	235 mm	125 mm	110 mm	£34.95
2073-7348	4	235 mm	161 mm	110 mm	£42.50
2073-7366	6	235 mm	197 mm	110 mm	£45.25

Arc Fault Detection Devices

- Built-in LED indicator shows fault status
- Combines arc fault detection with RCBO functions
- Series and parallel arc fault detection
- Sensitivity: 30 mA [6 kA]
- Mounted: DIN rail
- BS EN 62606



18th
EDITION



Includes:

- Prewired neutral cable

Code	Current Rating	1+
B Curve 6 kA – Type A		
2577-8644	6A	£99.95
2577-8704	16A	£99.95
2577-8710	20A	£99.95
2577-8722	32A	£99.95
2577-8728	40A	£99.95

Bi-Directional Single Pole Single Module Compact RCBOs

- Integrates residual and overcurrent protection in one device
- Incoming cables can be connected at the top or bottom with bi-directional protection
- Built-in switched neutral
- Test button and trip indicator
- Sensitivity: 30 mA [6 kA]
- Mounted: DIN rail



NEW

Code	Current Rating	1+
B Curve 6 kA		
2797-8712	6A	£15.95
2797-8697	16A	£15.95
2797-8706	32A	£15.95
2797-8709	40A	£15.95

Same day range

Almost 3,000 everyday essential products available in branch to take away today



ELECTRICITY METERS

45A Single Phase Single Module Energy Meter

- Designed to measure and display active energy consumption [kWh] within a consumer unit or modular enclosure
- Self-supplied
- Blue, easy-to-read backlit display
- Impulse constant: 1,000 imp / kWh
- Voltage rating: 230V
- MID B and D Certified
- Mounted: DIN rail
- EN 50470-1-3

MCG
INDUSTRIAL

Code	1+
0702-9838	£34.50

100A Single Phase Electricity Meter

- Accurately measures and displays active energy consumption [kWh] in a compact, surface mounted enclosure
- Large, easy-to-read LCD can be configured to auto-cycle any of the available registers or remain static
- Optical port for configuration or meter reading
- Highly reliable and capable of withstanding high voltage events and overcurrent without failure
- Tamper resistant with reverse-energy fraud detection and sealing for life
- MID Certified
- EN 50470-1-3

MCG
INDUSTRIALONLY
£49.25
+VAT

Code	Height	Width	Depth	1+
2027-1052	91 mm	125 mm	40 mm	£49.25

ROTARY ISOLATOR SWITCHES

Enclosed Rotary Isolators IP65

- Flame-retardant ABS plastic
- Easy access and switch removal
- Current rating: AC21 [resistive loads]
- Padlockable in the Off position
- Cable entry: 20 mm[Ø] Knockouts
- Mounted: Surface
- BS EN 60947-3

Code	Current Rating	Height	Width	Depth	1+
3 Pole					
0576-1585	20A	125 mm	100 mm	74 mm	£20.05
0433-2007	32A	125 mm	100 mm	74 mm	£26.25
1462-6486	40A	125 mm	100 mm	74 mm	£31.75
0433-2019	63A	175 mm	125 mm	90 mm	£34.65
4 Pole					
0576-1588	20A	125 mm	100 mm	74 mm	£21.50
0433-2013	32A	125 mm	100 mm	74 mm	£28.50
1462-6492	40A	125 mm	100 mm	74 mm	£35.95
0433-2025	63A	175 mm	125 mm	90 mm	£36.95

MAINS ISOLATOR SWITCH FUSES

SP+N Mains Isolator Switch Fuse

- Robust metalclad enclosure
- M20 and M25 knockouts top and bottom
- Five terminal earth bar
- IP20
- BS EN 61439-3

Includes:

- 100A 2 Pole isolator
- Fuse carrier
- 63A HRC ME Fuse
- 80A HRC ME Fuse
- 100A HRC ME Fuse

MCG
INDUSTRIALONLY
£54.95
+VAT

Code	Current Rating	Height	Width	Depth	1+
Single Pole + N					
2302-9522	63A / 80A / 100A	225 mm	115 mm	82 mm	£54.95

INDUSTRIAL SWITCHGEAR

TP+N Metal Switch Fuses

- Robust metalclad enclosure
- M20 and M25 knockouts top and bottom
- Five terminal earth bar
- IP20
- BS EN 61439-3

MCG
INDUSTRIAL

Includes:

- BS 88 Bolt-in fuses

Code	Current Rating	Height	Width	Depth	1+
3 Pole + N					
2453-6014	200A	500 mm	400 mm	200 mm	£924.95
2453-6017	250A	500 mm	400 mm	200 mm	£964.95
2453-6020	315A	800 mm	600 mm	300 mm	£1,347.50
2453-6023	400A	800 mm	600 mm	300 mm	£1,446.95

ROTARY ISOLATOR SWITCHES

Enclosed Rotary Isolators IP65

- Flame-retardant ABS plastic
- Easy access and switch removal
- Current rating: AC21 [resistive loads]
- Padlockable in the Off position
- Cable entry: 20 mm[Ø] Knockouts
- Mounted: Surface
- BS EN 60947-3

Code	Current Rating	Height	Width	Depth	1+
3 Pole					
0576-1585	20A	125 mm	100 mm	74 mm	£20.05
0433-2007	32A	125 mm	100 mm	74 mm	£26.25
1462-6486	40A	125 mm	100 mm	74 mm	£31.75
0433-2019	63A	175 mm	125 mm	90 mm	£34.65
4 Pole					
0576-1588	20A	125 mm	100 mm	74 mm	£21.50
0433-2013	32A	125 mm	100 mm	74 mm	£28.50
1462-6492	40A	125 mm	100 mm	74 mm	£35.95
0433-2025	63A	175 mm	125 mm	90 mm	£36.95

FROM
£20.05
+VAT

ROTARY ISOLATOR SWITCHES

Enclosed Rotary Isolators IP65

- Flame-retardant ABS plastic
- Easy access and switch removal
- Current rating: AC21 [resistive loads]
- Padlockable switch
- Cable entry: 20 mm[Ø] Knockouts
- Mounted: Surface
- BS EN 60947-3



MCG
INDUSTRIAL

Code	Current Rating	Height	Width	Depth	1+
4 Pole					
1462-6426	100A	280 mm	190 mm	130 mm	£98.25

FOOT & PALM SWITCHES

Emergency Stop Switches

- Surface mounted, insulated emergency stop switch
- Mushroom head: 90 mm[Ø]
- Operating temperature: -25 to 70°C
- Mechanical durability: 300,000 Operations
- BS EN 60947-5-1



MCG
INDUSTRIAL

Code	Contact Configuration	Operation	Colour	1+
IP65				
1442-5978	1 NC	Pull Release	Red / Yellow / Grey	£43.50
1442-5984	2 NC	Pull Release	Red / Yellow / Grey	£43.50

FIRE ALARM ACCESSORIES

Fireman's Switch

- Die-cast aluminium switch disconnecter
- Operates with fireman's hook or axe – pull down to switch Off
- Two-handed switch On
- 25A 2 Pole 230V AC
- Cable entry: 2 x M25 Glands top and bottom
- IP54
- IEC 60947-1 and 3
- Guarantee: 1 Year



MCG
INDUSTRIAL

Includes:

- PE Terminal and membrane gland [IP54]
- 'Fireman Switch' label
- 4 x M25 Sealing plugs



Code	1+	3+
2296-2532	£196.95	£192.50

PUSHBUTTONS & STATIONS

Made Up Pushbutton Stations IP65

- Pre-assembled pushbutton stations complete with contact blocks
- 10A at 230V AC, 3A at 24V DC
- Mounted: Surface
- BS EN 60947-5-1



FROM
£27.95
+VAT

Code	Colour	Contact Configuration	Operation	1+
Plastic				
0013-6954	Yellow	1 NC	Emergency Stop, Twist Release	£27.95
0013-6960	Yellow	1 NC	Emergency Stop, Key Release	£36.75

10A Emergency Stop Pushbuttons IP65

- Suitable for panel door and enclosed control station mounting
- Mushroom head
- Complete with mounting coupler and contact block
- Cut out: 22.5 mm[Ø]
- IP65 [when assembled]
- BS EN 60947-5-1



MCG
INDUSTRIAL

Includes:

- 2 x Keys [0043-7353 only]

Code	Operation	Contact Configuration	1+
0043-7377	Twist Release	1 NC	£19.95

PVC ADAPTABLE BOXES

Empty Enclosures IP66

- Screw-on flat lid
- Plain sides

2094-6730

MCG
INDUSTRIAL

FROM
£4.90
+VAT

Code	Colour	Length	Width	Depth	Price			
Stainless Steel Screws								
2094-6730	Black	100 mm	100 mm	50 mm	1+	£4.90	5+	£4.70
1866-0130	Grey	110 mm	150 mm	70 mm	1+	£7.95	5+	£7.75
1900-2097	Grey	145 mm	190 mm	72 mm	1+	£14.75	5+	£14.55
1868-7352	Grey	190 mm	243 mm	90 mm	1+	£24.75	5+	£23.95
Nylon Screws								
1829-8504	Grey	220 mm	300 mm	120 mm	1+	£36.25	5+	£35.50

DIN RAIL ENCLOSURES & ACCESSORIES

Plastic DIN Rail Enclosures IP65

MCG
INDUSTRIAL

- Manufactured from tough, flame retardant ABS
- Multiple knockouts for cable entry
- Snap closing top hinged, tinted front window
- Will fit a range of modular devices
- BS EN 60529

Includes:

- DIN rail


ONLY
£25.25
 +VAT

Code	No. of Modules	Height	Width	Depth	1+
Top Hinged Door – Grey					
1868-7415	5	158 mm	118 mm	92 mm	£25.25

ENCLOSURES

Sheet Steel Enclosures with Mounting Plates IP65

MCG
INDUSTRIAL

- Galvanised sheet steel enclosure with polyurethane gasket for improved durability
- Recessed gland plate, top or bottom, and reversible door with T-bar lock
- KEMA Certification
- BS EN 60529

Includes:

- Zinc-plated backplate [2 mm]
- Mounting kit
- Key


FROM
£97.95
 +VAT

Code	Height	Width	Depth	1+	3+
1434-9454	400 mm	300 mm	200 mm	£97.95	£92.95
1434-9457	400 mm	400 mm	200 mm	£116.75	£111.75

Stainless Steel Enclosures with Mounting Plates IP65

MCG
INDUSTRIAL

- Grade 304 stainless steel enclosure with polyurethane gasket for improved durability
- Reversible door hanging with standard stainless steel lock
- KEMA Certification
- BS EN 60529

Includes:

- Zinc-plated backplate [2 mm]
- Key



Code	Height	Width	Depth	1+	3+
1434-9481	400 mm	400 mm	200 mm	£224.75	£219.75

INDUSTRIAL PLUGS & SOCKETS

230V Plugs & Sockets IP44

MCG
INDUSTRIAL

- Corrosion and impact-resistant thermoplastic
- Operating temperature: -25 to 50°C
- IEC 60309-1 and 2


FROM
£3.95
 +VAT

Code	Current Rating	Type	Price		
2P+E 3 Pin					
2073-6742	16A	Plug – Cable Gland	1+	£3.95 10+	£3.80
2070-9226	16A	Coupler – Cable Gland	1+	£4.05 10+	£3.85
2070-9220	32A	Plug – Cable Gland	1+	£8.50 5+	£8.25
2070-9244	32A	Coupler – Cable Gland	1+	£10.80 5+	£10.45

110V Plugs and Sockets IP44

MCG
INDUSTRIAL

- Corrosion and impact-resistant thermoplastic
- Operating temperature: -25 to 50°C
- IEC 60309-1 and 2



Code	Current Rating	Type	Price		
2P+E 3 Pin					
2070-9208	16A	Plug – Cable Gland	1+	£3.55	10+ £3.40
2070-9223	16A	Coupler – Cable Gland	1+	£4.05	10+ £3.85

415V Plugs IP44

MCG
INDUSTRIAL

- Corrosion and impact-resistant thermoplastic
- Operating temperature: -25 to 50°C
- IEC 60309-1 and 2



Code	Current Rating	Type	Price		
3P+N+E 5 Pin					
2070-9214	16A	Plug – Cable Gland	1+	£6.35	10+ £6.10
2070-9232	32A	Plug – Cable Gland	1+	£10.50	5+ £9.95

Open an account
 Online or in branch

INDUSTRIAL PLUGS & SOCKETS

230V Interlocked Switched Socket IP44

MCG
INDUSTRIAL

- Corrosion and impact-resistant thermoplastic
- Padlockable rotary switch
- Operating temperature: -25 to 40°C
- IEC 60309-1, 2 and 4



Code	Current Rating	1+	3+
2P+E 3 Pin			
1453-9165	16A	£39.50	£37.50

415V Interlocked Switched Sockets IP44

MCG
INDUSTRIAL

- Corrosion and impact-resistant thermoplastic
- Padlockable rotary switch
- Operating temperature: -25 to 40°C
- IEC 60309-1, 2 and 4



Code	Current Rating	1+	3+
3P+N+E 5 Pin			
1453-9180	32A	£58.95	£56.95

FLEXIBLE CONDUIT & ACCESSORIES

Polypropylene Contractor Packs

MCG
INDUSTRIAL

- Self-extinguishing, low smoke and fume
- UV Stabilised
- Temperature range: 0 - 95°C
- IP51
- BS 4607



Pack contents:

- 10 m Conduit
- 10 x Glands and locknuts

FROM
£15.65
+VAT

Code	Ø	Colour	1+	5+
0013-6879	20 mm	Black	£15.65	£14.65
0013-6885	25 mm	Black	£29.25	£28.25

SAFETY LOCKOUT KITS & ACCESSORIES

Personal Lockout Kit

MCG
INDUSTRIAL

Kit includes:

- Red safety padlock (1 key)
- Aluminium MCB toggle lockout
- Universal MCB lockout
- Reusable lockout tag
- Cable ties
- Mini pouch



Code	1+
2483-8705	£18.25

Contractor Lockout Kit

MCG
INDUSTRIAL

- Ideal for a contractor working on commercial, industrial or domestic installations and routine maintenance schedules



Kit contents:

- Red safety padlock (1 key)
- Grip tight MCB lockout (over toggle)
- Grip tight MCB lockout (sideways)
- Plunge MCB lockout (pin-in)
- Plunge MCB lockout (pin-out)
- Universal MCB lockout
- Steel lockout hasp
- 5 x Reusable lockout tags
- 5 x Cable ties
- Non-permanent pen
- Zipped carry bag



2483-8717

ONLY
£65.95
+VAT

Need a product datasheet?

Download at cef.co.uk

Free Lighting Design Service

Exclusively from Fusion Luminaires

Our comprehensive service includes:

-  **Plans**
Product overview, representational floor plan and placement references.
-  **Results Overview**
Illumination levels and product requirements for individual rooms.
-  **Optional 3D Renderings**
Visual representation of the final installation.
-  **Full Product Specifications**
Detailed specs for all products used.
-  **Optional Energy Savings Report**
Showcase usage and potential monetary savings.



Transform your space with our expert lighting design!

Follow us on



FUSION
Luminaires

RELUX
light simulation tools



YOUR
ELECTRICAL
EXPERTS

Contact your local branch for more details

